





46020 Wireless Radiant Thermostat

| Job or Customer | | | |
|-----------------|---|------|--|
| Location | | | |
| Engineer | | | |
| Contractor | | | |
| SALUS Rep | | | |
| Submitted by | D | Date | |
| Approved by | D | Date | |

The 46020 Wireless Radiant Thermostat communicates wirelessly with the SALUS Wireless System to monitor and maintain the temperature of the space being heated. This thermostat will can be set up in systems with 46021/4/6 or 46028 Wiring Centers/Relay Controllers, 46027 radiator valve actuators or 46029 receivers. The battery operated 46020 thermostat can also setup and run an internal set-point schedule and monitor an external temperature sensor as an ambient or floor sensor.





| Features | Specifications | | | | | |
|--|-----------------------|---|--------|--------|----------------|--|
| Built-in wireless communication support Optional web- connected mode Floor protection when floor sensor is used Automatic freeze protection Three schedule modes, 6 periods per schedule Remote or local schedule setup 6-button touch keypad Local or remote initiated keylock 1.5 year expected battery life | Model | AWRT10RF Wireless Radiant Thermostat | | | | |
| | Package Dimensions | Length | Width | Height | Package Weight | |
| | | 6.18″ | 2.8″ | 1.45″ | 0.5 Lbs | |
| | | 15.7 cm | 7.2 cm | 3.7 cm | 230 g | |
| | Enclosure Material | White PC/ABS Plastic | | | | |
| | Approvals | Meets Class B ICES & FCC Part 15 | | | | |
| | Operating Temperature | Indoor use only, 32 to 122°F (0 to 50°C), RH <90% noncondensing | | | | |
| | Storage Temperature | 14 to 140°F (-10 to 60°C) | | | | |
| | Power Supply | 2 x AA alkaline batteries | | | | |
| | | Internal thermistors, 10 k Ω @ 77°F (25°C) \pm 0.2°C | | | | |
| | Temperature Sensor | Measurement Range: 32 - 99°F (0 - 40°C) | | | | |
| | | Resolution: 1°F (0.5°C) | | | | |
| | User Interface | Set Point Range Heating: 41 - 92°F (5 – 33.5°C) / Cooling: 44 - 95°F (6.5 - 35°C) | | | | |
| | | Indications: Temperature, Day of the Week, Heat/Cool, Settings, Key Lock | | | | |
| | | Backlit fixed segment LCD Display, User settings stored in non-volatile memory | | | | |



46020 Wireless Radiant Thermostat





| Compatible Equipment | | |
|----------------------|--|--|
| 46025 | Basic Gateway | |
| 46021 | 1-Zone Pump Wiring Center/Relay Controller | |
| 46024 | 4-Zone Pump Wiring Center/Relay Controller | |
| 46026 | 6-Zone Pump Wiring Center/Relay Controller | |
| 46028 | Zone Valve Wiring Center/Relay Controller | |
| 46027 | Wireless Radiator Valve Actuator - Hot Water | |
| 46029 | Zigbee Receiver | |



850 Main Street Redwood City, CA 94603